



HORIZONTAL AXIS WIND TURBINE **Note : Option C is recommended for operation**

RE570



Year 1
study

Features

- Variable Blade quantity
- Allows Investigation of an Efficient Three Phase to DC Horizontal Axis Wind Turbine
- Safe and Suitable For Student Operation.
- Instrumentation Allows Detailed Analysis of Turbine and Generator Performance.
- Optional Mast for Controlled Testing
- Optional Computerised Data Acquisition Upgrade

Description

In the field of renewable energy, wind power generation represents one of the most universally available sources of electrical energy. It is important that students understand the factors that affect turbine and generator performance.

The Hilton Horizontal Axis Wind Turbine RE570 allows

students to investigate the performance of a typical small scale 3 phase to DC wind generator. The unit will provide interesting and instructive experimental work for all students.

A small diameter horizontal axis wind turbine with 3 phase generator and integral DC rectification. The unit is supplied with a small mounting 'stub' mast for installation at an elevated height. Alternatively the unit may be mounted on a locally available mast or the optional RE570C for examination by students.

The unit may be operated into the battery charge controller supplied and a variable load for performance investigation. The number of blades may be varied for performance investigation.

The instrumentation and control console supplied allows measurement of electrical power output, turbine speed

and variation of applied load. The air velocities before and after the turbine is measured in order to allow students to investigate the overall performance of the unit.

Related laws

- Renewable Energy
- Aerodynamics
- Thermodynamics
- Energy Conservation
- Mechanical Engineering
- Fluid Mechanics

Learning capabilities

- Measurement of wind speed turbine speed and power generation relationship.
- Measurement of air velocity before and after the turbine.
- Calculation of theoretical power.

Technical Specification

- Turbine Diameter: Ø910mm
- Standard number of Blades: 6
- 3 phase generator
- Mounting stub: 500mm long
- AC to DC generation
- Air velocity sensor before turbine
- Air velocity sensor after turbine
- External loading up to 15A

Recommended Ancillaries

- RE570B
- RE570C

What's in the Box?

- 1 x RE570
- 1 x Control console
- 1 x 12V battery
- Spare fuses
- Instruction manual
- Packing list

- Test sheet

Weights & Dimensions

- Weight: 20 kg
- Length: 910mm
- Width: 610mm
- Height: 1000mm

Essential Services

- 220-230 Volts, Single Phase, 50Hz (With earth/ground)
- Line current up to 5A at 230v.
- 110-120 Volts, Single Phase, 60Hz (With earth/ground)
- Line current up to 10A at 110v.

Ordering information

To order this product, please call PA Hilton quoting the following codes:

RE570
RE570/230/RC
RE570/115/RC

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 2 YEARS