



## TORSIONAL OSCILLATION MODULE (FREE & FORCED) HVT12B



1  
study

### Features

- Allows for different conditions to be applied to all four wire specimens
- Two steel specimens,  $\text{Ø}3.175\text{mm}$  &  $\text{Ø}4.75\text{mm}$
- Two brass specimens,  $\text{Ø}3.175\text{mm}$ ,  $\text{Ø}4.75\text{mm}$
- Upper and lower supports allow differing end conditions to be applied: Fixed/Fixed, Fixed/Free,

### Description

The HVT12B allows a number of torsional experiments to be applied to rod specimens. A vertical backboard is fixed to the HVT12F (not supplied), and assists the securing of the top end of the rod. Along the length of the rod can be attached a solid disc. Additionally a solid ring and split ring are included, that can rest onto the disc to increase the overall inertia.

Different end conditions can be introduced by allowing the bottom end of the wire to be free or clamped, thus

stiffening the rod specimen.

The bottom end clamp has the ability to shorten the rod length and vary the experimental parameters.

A torsion system is supplied that allows the rod to be twisted at set intervals against a protractor.

A support frame, damping cylinder and tank enable controlled damping to be applied.

Includes steel and brass rods complete with clamps and adaptors.

### Related laws

- Torsion
- Torsional stiffness
- Resonance
- Multi-mass torsional systems
- Rotational Machinery
- Dynamics
- Automotive

### Learning capabilities

- To show periodic time is proportional to square root of rod length
- To show periodic time is proportional to square root of mass moment of inertia
- To show periodic time is inversely proportional to square root of rod diameter
- To show periodic time is inversely proportional to square root of modulus of rigidity
- Study the decay in amplitude of a damped oscillation

### Technical Specification

- Two steel specimens,  $\text{Ø}3.175\text{mm}$  &  $\text{Ø}4.75\text{mm}$ ; 1200(L)mm
- Solid Disk:  $\text{Ø}250 \times 30\text{(t)}\text{mm}$ , steel, 11.5kg (approx)
- Ring:  $\text{Ø}250 \text{ O.D} \times \text{Ø}160 \text{ i.d} \times 30\text{(t)}\text{mm}$ , steel, 4.5kg (approx)
- Split ring:  $\text{Ø}250 \text{ O.D} \times \text{Ø}160 \text{ i.d} \times 40\text{(t)}\text{mm}$ , steel, 8.75kg (approx)
- Protractor scale:  $\pm 30^\circ$ , 1 degree increments

### Essential Ancillaries

- Requires HVT12F for operation

### What's in the Box?

- 1 x Upper support
- 1 x lower support
- 1 x Rotational scale
- 4 x Specimen rods
- 1 x Solid disc
- 1 x Ring
- 1 x Split ring
- 1 x Damping Tank
- Stop watch
- 2 x Hanger
- 4 x 1N weight
- 2 x 5N weight
- Tape measure
- Instruction Manual
- Packing list
- Test Sheet

### Weights & Dimensions

- Weight: 33Kg
- Length: 1310mm
- Width: 350mm
- Height: 380mm

### Essential Services

- HVT12F

### Ordering information

To order this product, please call PA Hilton quoting the following code:  
HVT12B

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2018 P.A. Hilton Limited. All rights reserved. This technical leaflet, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of P. A. Hilton Limited. Hi-Tech Education is a registered trade mark of P. A. Hilton Limited.

COUNTRY OF ORIGIN - UK WARRANTY PERIOD - 2 YEARS